



Geberit Bambini washbasin tap, battery operation



APPLICATION PURPOSES

- For children
- For childcare
- For installation in washbasins or washtops
- For installation in Bambini play and washspaces
- For connecting cold and hot water
- For combination with continuous flow heater, see technical data sheet "Washbasin taps with instantaneous water heaters"

CHARACTERISTICS

- Child-friendly design
- Tap group I in accordance with DIN 4109
- Infrared user detection
- Warning when the battery is low
- Adjustable activation distance
- Interval flush
- Flush actuation for basin cleaning can be deactivated manually
- With integrated check valve

- Chrome-plated housing
- Hat made of polycarbonate

TECHNICAL DATA

Battery type	CR-P2 (6 V)
Protection degree	IP65
Operating voltage	6 V DC
Operating pressure	1–8.5 bar
Differentiated pressure CW/WW max.	1.5 bar
Test pressure, water max.	16 bar
Test pressure, air / inert gas max.	3 bar
Operating temperature, water, short-term max.	80 °C
Flow rate at 3 bar	5.7 l/min
Interval flush	24 h
Interval flush time	10 s
Product material	Brass

SCOPE OF DELIVERY

- Battery compartment
- Lithium battery, type CR-P2, 6 V
- Basket filter
- Tap aerator key
- Fastening material

ACCESSORIES

- Geberit Bambini mini thermostat for washbasin tap
- Geberit Bambini tap aerator for washbasin tap

INFO

- It is recommended to use the Geberit Bambini mini thermostat for washbasin taps in order to avoid scald injuries
- If the washbasin tap Bambini is used in the upper basin of a play and washspace Bambini in combination with a overflow pipe, the swiveling tap aerator for Geberit washbasin tap Bambini (art. no. 571410000) must be ordered separately

Art. no.	Colour / surface	Mixer	B cm	H cm	T cm	
116.208.21.1 Phasing out	Body: chrome / Glossy Hat: dust grey RAL 7037	with mixer	8	12.6	12.4	